

मिश्रा धातु निगम लिमिटेड  
(भारत सरकार का उपक्रम)  
(एक मिनी रत्ना कंपनी)  
सुपर अलॉय प्लांट  
इकाई : कान्चनबाग, हैदराबाद - 500058 भारत  
दूरभाष : 24340001 (लाइन 10)  
फैक्स : 040-24340764,  
ई-मेल : mohanty.midhani@nic.in



MISHRA DHATU NIGAM LIMITED  
(A Govt. of India Enterprise)  
(A MINI RATNA COMPANY)  
SUPERALLOYS PLANT  
P.O. Kanchanbagh, Hyderabad - 500 058, India  
Phone : 24340001 (10 Lines)  
Fax : 040-24340764,  
E-mail : mohanty.midhani@nic.in

26.07.2017

**CORRIGENDUM -I**

**Tender Title : MODIFICATION AND EXTENSION OF FORGE LEAN TO ROOF, KANCHANBAGH, HYDERABAD**

**Tender ID :**

**Tender Ref. No :** MDN/ AP2071025/E- ADVT/091/17-18 Date:- 11-07-2017

**Corrigendum Title : ESTIMATE VALUE AND BOQ ITEM IN THE TENDER**

This has reference to subject tender. The Corrigendum to the subject tender is hereby issued. All Participating bidders are requested to note the changes in respect of the subject tender.

Sl. No.	Tender Document Reference	To be Read As
1.	Estimated cost projected Rs 74.14 lakhs.	Estimates Cost Rs 82.38 lakhs
2	Earnest Money Deposit (EMD) Rs 1.85 lakhs	Earnest Money Deposit ( EMD) Rs 2.06 lakhs
	<b>BOQ Item</b>	
3	<b>Item 19 (a)</b> a) Supply & Fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-incharge) 6 mm ± 5% total coated thickness (TCT), Zinc coating 120gsm as per IS 277 in 240 Mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12m or as desired by E-I-C. The sheet shall be fixed using self drilling / self tapping screws of size 5.5 x 55mm with EPDM seal complete. Also the L-flashings, corner trims and barge boards are to be carried out with similar sheeting	<b>Item 19(a)</b> a) Supply & Fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-incharge) 26 guage or 0.40 mm ± 5% total coated thickness (TCT), Zinc coating 120gsm as per IS 277 in 240 Mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12m or as desired by E-I-C. The sheet shall be fixed using self drilling / self tapping screws of size 5.5 x 55mm with EPDM seal complete. Also the L-flashings, corner trims and barge boards are to be carried out with similar sheeting
4	<b>Item 27( a)</b> a) Supply & Fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-incharge) 6 mm ± 5%	<b>Item 27 (a)</b> a) Supply & Fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-incharge)

<p>total coated thickness (TCT), Zinc coating 120gsm as per IS 277 in 240 Mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12m or as desired by E-I-C. The sheet shall be fixed using self drilling / self tapping screws of size 5.5 x 55mm with EPDM seal complete. Also the L-flashings, corner trims and barge boards are to be carried out with similar sheeting complete</p>	<p>26 guage or 0.40 mm <math>\pm</math> 5% total coated thickness (TCT), Zinc coating 120gsm as per IS 277 in 240 Mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12m or as desired by E-I-C. The sheet shall be fixed using self drilling / self tapping screws of size 5.5 x 55mm with EPDM seal complete. Also the L-flashings, corner trims and barge boards are to be carried out with similar sheeting complete</p>
--	--

**NOTE:** HENCE IT IS ADVISED THAT THE ABOVE MAY PLEASE BE TAKEN INTO CONSIDERATION WHILE SUBMITTING YOUR OFFER.

*[Signature]*  
AGM (I/c Purchase)